

FLATTEX

Wrapped Flat Drain



PRODUCT CHARACTERISTICS

Description	Recycled HDPE corrugated flat pipe (4cm thickness) with reinforced inside wall
References	FlatTex 170 NAD17025EN
Composition	HDPE (High Density polythene)
Colour	Black and white
Height	170 mm
Width	40 mm
Wall thickness	1,5 mm
Perforations	4 x 30 mm
Absorbtion surface	240 cm ² /ml
Packaging	Roll 25 ml
Roll dimensions	100 x 100 x 17 cm
Roll weight	17 kg

HYDRAULIC CHARACTERISTICS

Initial flowrate		Ø100 standard	FlatDrain 170
Third filling	l/min 1% slop	60	60
Capacity	l/min 1% slop	180	> 145
Flowrate in a pore	l/min	0,023	0,057
Flow speed	m/s	0,50	0,85

ACCESSORIES

	FlatDrain 170
Connector	NADMANC170
Tap	NADBOUC170
Ø100-125 Adaptor	NADADAP170
Double exit	NADSORL170
Universal junction	NADRUH3017

Production and quality: FLATTEX pipes are constantly tested according to DIN 4262/1 Standards



The application, use or transformation of our products are beyond our control and consequently cannot engage ATE's responsibility but the user's or the converter's.